



## UHD VANDALPROOF FIXED DOME SMD IR IU-MC4211



### MAIN FEATURES :

- 1 / 2, 9" SONY CMOS SENSOR
- 4 IN 1 : AHD / TVI / CVI / CVBS OUTPUT
  - 1080P RESOLUTION
- SUPPORT OSD & COAXIAL CONTROL
  - 2D & 3D DNR, BLC, D-WDR
  - LENS 3.6MM



| <b>IU-MC4211</b>               |   |
|--------------------------------|---|
| <b>Camera</b>                  |   |
| Image Sensor                   | 1/2.9" SONY CMOS Sensor   |
| Signal System                  | NTSC/PAL  |
| Effective Pixels               | 1920(H) x 1080(V)   |
| Electronic Shutter             | AUTO/ 1/50 (1/60) -1/50,000sec  |
| Synchronization                | External  |
| Min. Illumination              | 0.01Lux   |
| Video Frame Rate               | PAL/NTSC:25/30fps   |
| Video Output                   | AHD / TVI / CVI / CVBS  |
| <b>Camera Features</b>         |   |
| S/N Ratio                      | >41dB   |
| Noise Reduction                | 2D&3D DNR   |
| Day&Night                      | Color / B&W/ AUTO / EXT   |
| White Balance                  | Auto / Manual/Indoor/Outdoor  |
| OSD                            | English / Chinese / German / French / Italian / Spanish / Polish / Russian / Portuguese / Dutch / Turkish |
| AGC                            | 13 ( 0~15 )   |
| IR LED                         | 14 $\mu$ X18pcs SMD LED   |
| IR Range                       | up to 25m   |
| <b>Lens</b>                    |   |
| Focal Length                   | 3.6mm Fixed lens  |
| Angle of View                  | H: 80°  |
| Lens Type                      | Fixed Iris  |
| Mount Type                     | M12 & Metal Housing   |
| <b>General</b>                 |   |
| IP Rating                      | IP66  |
| Power Supply                   | DC12V(+/-10%)   |
| Power Consumption              | IR OFF:77mA / IR ON:250mA   |
| Working Temperature / Humidity | -20~+50°C RH95% MAX   |
| Dimensions(WxDxH)              | ∅ 114 X 83 (H) mm   |
| Weight                         | 350g  |