

AHD Motorized Zoom Bullet Camera

KC-KF200EAHD



FEATURES

- 1/3" 2.0 MP Sony IMX322 CMOS Sensor
- OSD Menu, control over coaxial cable
- 25/30FPS realtime output, no delay, loss-less, over 500m transmission
- Day/Night(ICR), AWB, AGC, BLC, 3D-DNR, Intelligent IR
- Support Optical zoom and auto focus function



Specification

Model No	KC-KF200EAHD	
Image Sensor	1/3" 2.0 MP Sony IMX322 CMOS Sensor(IMX322+2440H)	
TV System	PAL / NTSC	
Effective Pixels	1920(H) × 1080(V)	
Mini. Illumination	0.01Lux@ (F1.2, AGC ON)	
Electronic Shutter	1/25s ~ 1/60000s Slow Shutter 2X--8X	
Video standard	AHD standard definition	
Video Frame Rate	1920 × 1080@25 fps 1920 × 1080@30 fps	
LED & IR Distance	ø 28mil X 4PCS Array LED Max IR View Distance 50M	
Day&Night	ICR	
Video Output	1CH BNC AHD output,Support Switch to Analog output	
OSD Menu	Support	
Functions	Exposure	AUTO/BLC
	White balance	AWB
	Day&Night	AUTO/ B/W /COLOR
	function set	3D Noise Reduction
	Advanced Function	3D-DNR,DWDR, anti-fog
	Image adjust	Sharpness/Saturation/Brightness
Transmission Distance	Over 500m via 75-3 coaxial cable	
Lens	2.8-12MM Varifocal Lens, Motorised Zoom lens	
Power Supply	DC 12V +/-15%	
Working Environment	-30° C~+60° C / Less than 95%RH (no condensation)	
Operating Temperature	-10°C to +50°C, RH 80% Max	
Storage temperature	-20°C to +60°C, RH 90% Max	
Storage temperature	-20°C to +60°C, RH 90% Max	
Dimension	287mm(L)*150mm(W)*150(H)mm	
Weight	980g	
Product Box Size	225mm*200mm*115mm	
Carton Size; Qty Of Package	580mm*380mm*480mm; 18PCS/CTN	

<http://www.keeper.cn>