



Features:

- ▣ Support AHD - TVI - CVI - IPC - Analog HD / 960H
- ▣ HDMI/VGA simultaneous video output;
- ▣ 1U Case, 1 SATA (Up to 6TB);
- ▣ 1*10/100Mbps auto-sensing Ethernet port, RJ45 port ;
- ▣ Automatic networking support, a key to add equipment;
- ▣ Cloud services, P2P, alarm information push to phone;
- Support remote access, support RTSP;
- ▣ Mobile phone remote monitoring (iOS, Android);
- ▣ Multi browser access (IE, Chrome, Firefox, Safari);
- ▣ Perfect protection circuit, unique triple watchdog function;
- Support WEB, CMS, Cloudsee Platform;

Model		TRI-VHR516	
Video	Codec	SMART H.264+	
	Encode	16*1080N @15fps	
	Decode	16*1080N @15fps	
	Multi-mode		Analog:16*4M-N
			Hybird: 8*4M-N + 8*2M(IP)
			IP:16*2M(IP)
Playback	16ch		
Audio	Compression	G.711a	
	Intercom	Support	
Management	Record mode	Manual>Alarm>Motion detection>Timing	
	Inquire mode	Inquire by Time/Calendar/Event/Channel	
	Storage Mode	HDD Storage	
	Backup	USB, SATA	
Interface	Interface	16*BNC(Support Coaxitron)	
	HDMI output	1*HDMI	
	VGA output	1*VGA	
	Audio I/O	2in, 1out	
	Alarm I/O	Optional	
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port	
	PTZ control	1*RS485, Support for multiple PTZ protocol	
	USB port	2*USB2.0 ports	
	HDD	1*SATA interface (Up to 6TB)	
General	Temperature	0°C- + 55°C	
	Humidity	10% -90% RH	
	Power supply	12V/2A	
	Consumption	<10W(Without HDD)	